



MANUFACTURER/ FACILITY	FILL HEIGHT TABLES RECEIVED	QUALIFIED SIZES OF AASHTO M252 PIPE	QUALIFIED SIZES OF AASHTO M294 PIPE	QUALIFIED SEALANT BRAND(S)	NTPEP PLANT AUDIT STATUS
<p><u>ADS/Hancor (cont.)</u></p> <p>Vicksburg, MS</p> <p>Winter Garden, FL</p> <p>Sebring, FL</p> <p>Waverly, NY</p> <p>Livermore, KY</p>					<p>Compliant-V</p> <p>Compliant-V</p> <p>Compliant-V</p> <p>Compliant-V</p> <p>Compliant-VR</p>
<p>Quality Culvert, Inc. 25726 CR 561 PO Box 435 Astatula, FL 34705-0435 (866)343-8488 FAX: (352)343-8422 Attn: Carl Tyner</p> <p>Astatula, FL</p> <p>Athens, AL</p>	<p>Yes</p>	<p>8" – Type S, SP 10" – Type S, SP</p>	<p>12" – Type S 15" – Type S 18" – Type S 24" – Type S 30" – Type S 36" – Type S 42" – Type S 48" – Type S</p>	<p>Hamilton Kent in Ontario, Canada (Tested to 10.8 psi)</p>	<p>Compliant-V</p> <p>Compliant-V</p>
<p>LANE Enterprises, Inc. 34 Strohm Road Shippensburg, PA 17257 (717) 532-5959 FAX (717) 532-7997 Attn: Mark Dick</p> <p>Shippensburg, PA</p>	<p>Yes</p>	<p>4" – Type C, CP 6" – Type C, CP, S, SP 8" – Type C, CP, S, SP 10" – Type C, CP, S, SP</p>	<p>12" – Type S, SP 15" – Type S, SP 18" – Type S, SP 24" – Type S, SP 30" – Type S, SP 36" – Type S, SP 42" – Type S, SP 48" – Type S, SP 60" – Type S, SP</p>	<p>Hamilton Kent in Ontario, Canada (Tested to 13 psi) 60 inch diameter tested with Spring Seal Gasket (Tested to 13 psi)</p>	<p>Compliant-V</p>

**QUALIFIED PRODUCTS LIST 30**

June 5, 2024

Page 3 of 4

<p>Southeast Culvert, Inc. 1094 Bankhead Highway Winder, GA 30680 (770)963-5041 Fax: (770)339-0240</p> <p>Winder, GA</p>	<p>Yes</p>	<p>8" – Type S, SP 10" – Type S, SP</p>	<p>12" – Type S, SP 15" – Type S, SP 18" – Type S, SP 24" – Type S, SP 30" – Type S, SP 36" – Type S, SP 42" – Type S, SP 48" – Type S, SP 60" – Type S, SP</p>	<p>Vertex, Inc. in Mogadore, OH (12, 15, 18, 24, 30, 36, 48 and 60 inch sizes tested to 13 psi with single gasket. 42, inch size requires double gasket for 13 psi)</p>	<p>Compliant-V</p>
<p>Blue Diamond Industries, LLC 3399 Tates Creek Road, Suite 110 Lexington, KY 40502 (859)224-0415 Fax: (859)224-0543</p> <p>Roseboro, NC</p>	<p>Yes</p>	<p>3" – Type C, CP 4" – Type C, CP, S, SP 6" –Type C, CP, S, SP 8" – Type C 10" – Type C</p>			<p>Compliant-V</p>
<p>Crumpler Plastic Pipe PO Box 2068 Roseboro, NC 28382-2068 1-800-334-5071 FAX: (910)525-5801</p> <p>Roseboro, NC</p>	<p>Yes</p>	<p>3" – Type C, CP 4" – Type C, CP, S, SP 5" – Type C, CP 6" Type C, CP, S, SP 7" – Type C, CP 8" – Type C, CP, S, SP 9" – Type C, CP 10" – Type C, CP, S, SP</p>	<p>12" – Type S 15" – Type S 18" – Type S 24" – Type S 30" – Type S 36" – Type S 42" – Type S 48" – Type S</p>	<p>Springseal, Inc. (Tested to 13 psi)</p>	<p>Compliant-V</p>
<p>Prinsco 1717 16<sup>th</sup> Street NE Wilmar, MN 56201 1-800-992-1725 1-320-222-6800</p> <p>Jesup, IA</p>	<p>Yes</p>	<p>GOLDFLO 4" – Type C, CP, S, SP 5" – Type C, CP 6" Type C, CP, S, SP</p>	<p>GOLDFLO 12" – Type C, CP, S, SP 15" – Type C, CP, S, SP 18" – Type S, SP 24" – Type S, SP 30" – Type S, SP 36" – Type S, SP</p>	<p>Springseal, Inc. (Tested to 13 psi)</p>	<p>Compliant-V</p>

Prinsco (Cont.) Chatsworth, IL		8" – Type C, CP, S, SP	42" – Type S, SP 48" – Type S, SP		Compliant-V
Fresno, CA		10" – Type C, CP, S, SP	54" – Type S, SP 60" – Type S, SP		Compliant-V
Prinsburg, MN					Compliant-V

NOTE: For the following counties: Berkeley, Beaufort, Charleston, Colleton, Dorchester, Georgetown, Horry, and Jasper, provide pipe that is listed with a joint test to 13 psi. For all other counties, use 10 psi minimum unless noted otherwise in the plans or special provisions.

SCDOT Contact: G. Michael Lockman, P.E.  
SCDOT Office of Materials and Research  
Columbia, SC 29202  
(803) 737-6692 • [LockmanGM@scdot.org](mailto:LockmanGM@scdot.org)